





- Type 1 + 2+3 AC surge protector
- Integrated surge counter
- VG Technology
- Iimp: 25 kA on 10/350µs impulse
- In: 25 kA
- Optimized to TOV
- No leakage current
- Monobloc
- Remote signaling
- EN 61643-11, IEC 61643-11 complied



	<b>Electrical Characteristics</b>																																																	
 <p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>1+2+3</td></tr> <tr><td>Network</td><td></td><td>230 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>TT-TNS</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>275 Vac</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac withstand</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 µs impulses</td><td>In</td><td>25 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>I<sub>max</sub></td><td>100 kA</td></tr> <tr><td>Impulse current by pole max. withstand 10/350µs by pole</td><td>I<sub>imp</sub></td><td>25 kA</td></tr> <tr><td>Total lightning current max. total withstand @ 10/350µs</td><td>I<sub>total</sub></td><td>50 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs</td><td>Uoc</td><td>6 kV</td></tr> <tr><td>Protection level L/N @ In (8/20µs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level N/PE @ In (8/20µs)</td><td>Up N/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I<sub>sc</sub></td><td>50 000 A</td></tr> </table>		SPD type		1+2+3	Network		230 V single-phase	AC system		TT-TNS	Max. AC operating voltage	Uc	275 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac withstand	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 µs impulses	In	25 kA	Max. discharge current max. withstand @ 8/20 µs by pole	I <sub>max</sub>	100 kA	Impulse current by pole max. withstand 10/350µs by pole	I <sub>imp</sub>	25 kA	Total lightning current max. total withstand @ 10/350µs	I <sub>total</sub>	50 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	6 kV	Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV	Protection level N/PE @ In (8/20µs)	Up N/PE	1.5 kV	Admissible short-circuit current	I <sub>sc</sub>	50 000 A
SPD type		1+2+3																																																
Network		230 V single-phase																																																
AC system		TT-TNS																																																
Max. AC operating voltage	Uc	275 Vac																																																
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac withstand																																																
Residual Current Leakage current to Ground	Ipe	None																																																
Follow current	If	None																																																
Nominal discharge current 15 x 8/20 µs impulses	In	25 kA																																																
Max. discharge current max. withstand @ 8/20 µs by pole	I <sub>max</sub>	100 kA																																																
Impulse current by pole max. withstand 10/350µs by pole	I <sub>imp</sub>	25 kA																																																
Total lightning current max. total withstand @ 10/350µs	I <sub>total</sub>	50 kA																																																
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	6 kV																																																
Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV																																																
Protection level N/PE @ In (8/20µs)	Up N/PE	1.5 kV																																																
Admissible short-circuit current	I <sub>sc</sub>	50 000 A																																																
<b>Mechanical Characteristics</b>																																																		
<table border="1"> <tr><td>Technology</td><td></td><td>VG Technology (MOV+GSG)</td></tr> <tr><td>SPD configuration</td><td></td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 2.5-25mm<sup>2</sup> (35mm<sup>2</sup> rigid)</td></tr> <tr><td>Format</td><td></td><td>Monobloc modular box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator - Red/Green</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Wiring for remote signaling</td><td></td><td>1.5 mm<sup>2</sup> max.</td></tr> <tr><td>Max. Voltage/Current for remote signaling</td><td></td><td>250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td></tr> </table>			Technology		VG Technology (MOV+GSG)	SPD configuration		Single phase	Connection to Network		By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)	Format		Monobloc modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator - Red/Green	Remote signaling of disconnection		Output on changeover contact	Wiring for remote signaling		1.5 mm <sup>2</sup> max.	Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)									
Technology		VG Technology (MOV+GSG)																																																
SPD configuration		Single phase																																																
Connection to Network		By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)																																																
Format		Monobloc modular box																																																
Mounting		Symmetrical rail 35 mm (EN 60715)																																																
Housing material		Thermoplastic UL94 V-0																																																
Operating temperature	Tu	-40/+85°C																																																
Protection rating		IP20																																																
Failsafe mode		Disconnection from AC network																																																
Disconnection indicator		1 mechanical indicator - Red/Green																																																
Remote signaling of disconnection		Output on changeover contact																																																
Wiring for remote signaling		1.5 mm <sup>2</sup> max.																																																
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																																
<b>Disconnectors</b>																																																		
<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td></td><td>SFD1-25S-11 / or Fuses Type gG 315 A</td></tr> </table>			Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		SFD1-25S-11 / or Fuses Type gG 315 A																																							
Thermal disconnector		Internal																																																
Installation ground fault breaker		Type 'S' or delayed																																																
Back-up protection device		SFD1-25S-11 / or Fuses Type gG 315 A																																																
<b>Standards</b>																																																		
<table border="1"> <tr><td>Standards compliance</td><td></td><td>EN 61643-11 / IEC 61643-11</td></tr> </table>			Standards compliance		EN 61643-11 / IEC 61643-11																																													
Standards compliance		EN 61643-11 / IEC 61643-11																																																
<b>Part number</b>																																																		
64191																																																		